



RADIO TEST REPORT

For

OAXIS ASIA PTE LTD

myFirst Fone R1s, S11

Test Model: KW1305, G4K1

Prepared for : OAXIS ASIA PTE LTD
Address : 31 Woodlands Close #01-22 Singapore 737855

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : Room 101, 201, Building A and Room 301, Building C, Juji
Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District,
Shenzhen, Guangdong, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : June 23, 2020
Number of tested samples : 1
Serial number : Prototype
Date of Test : June 23, 2020 ~ July 03, 2020
Date of Report : July 01, 2022



Scan code to check authenticity

**RADIO TEST REPORT****ETSI EN 301 908-2 V11.1.2 (2017-08)**

IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU; Part 2: CDMA Direct Spread (UTRA FDD) User Equipment (UE)

Report Reference No. : LCS200617016AEG001

Date of Issue : July 01, 2022

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

**Testing Location/ Procedure : Full application of Harmonised standards ☒
Partial application of Harmonised standards ☐
Other standard testing method ☐**

Applicant's Name : OAXIS ASIA PTE LTD

Address : 31 Woodlands Close #01-22 Singapore 737855

Test Specification

**Standard : ETSI EN 301 908-1 V13.1.1 (2019-11)
ETSI EN 301 908-2 V11.1.2 (2017-08)**

Test Report Form No. : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2017-06

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description. : myFirst Fone R1s, S11

Trade Mark : MyFirst, UMEOX

Test Model : KW1305, G4K1

Ratings : DC 3.7V by Rechargeable Li-Polymer Battery(580mAh)

Result : Positive

Compiled by:

Vera Deng/ Administrators

Supervised by:

Cary Luo/ Technique principal

Approved by:

Gavin Liang/ Manager



RADIO -- TEST REPORT

Test Report No. : LCS200617016AEG001	<u>July 01, 2022</u> Date of issue
---	---------------------------------------

Test Model.....	: KW1305, G4K1
EUT.....	: myFirst Fone R1s, S11
Applicant.....	: OAXIS ASIA PTE LTD
Address.....	: 31 Woodlands Close #01-22 Singapore 737855
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: OAXIS ASIA PTE LTD
Address.....	: 31 Woodlands Close #01-22 Singapore 737855
Telephone.....	: /
Fax.....	: /
Factory.....	: OAXIS ASIA PTE LTD
Address.....	: 31 Woodlands Close #01-22 Singapore 737855
Telephone.....	: /
Fax.....	: /

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Revision History

Revision	Issue Date	Revisions	Revised By
000	January 26, 2022	Initial Issue	Gavin Liang
001	July 01, 2022	See Remark	Gavin Liang

Remark:

1. Declared by applicant, Model/Type reference of the product is modified from “KW1305M” to “KW1305”, other information and results contained in this report are not changed, original test report become invalid.
2. Declared by applicant, require to re-sign the test report, “Date of issue” is replaced from “January 26, 2022” by “July 01, 2022”, other information and results contained in this report are not changed, original test report become invalid.



TABLE OF CONTENTS

1. GENERAL INFORMATION.....	6
1.1. PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2. SUPPORT EQUIPMENT LIST.....	9
1.3. EXTERNAL I/O	9
1.4. OBJECTIVE	9
1.5. TEST CONDITIONS	9
1.6. DESCRIPTION OF TEST MODE	10
1.7. MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	10
1.8. DESCRIPTION OF TEST FACILITY	10
2. SYSTEM TEST CONFIGURATION.....	11
2.1. JUSTIFICATION	11
2.2. EUT EXERCISE SOFTWARE	11
2.3. SPECIAL ACCESSORIES.....	11
2.4. BLOCK DIAGRAM/SCHEMATICS	11
2.5. EQUIPMENT MODIFICATIONS	11
2.6. TEST SETUP.....	11
3. SUMMARY OF TEST RESULTS	12
4. LIST OF MEASURING EQUIPMENT	14
5. PHOTOGRAPHS OF TEST SETUP.....	15
6. PHOTOGRAPHS OF THE EUT	15



1. GENERAL INFORMATION

1.1. Product Description for Equipment Under Test (EUT)

EUT : myFirst Fone R1s, S11
Test Model : KW1305, G4K1
Power Supply : DC 3.7V by Rechargeable Li-Polymer Battery(580mAh)
Hardware Version : HK839_MB_V1.0
Software Version : k11_V1.0.0

2G :

Support Band : ☒ GSM 900 (EU-Band) ☒ DCS 1800 (EU-Band)
☒ GSM 850 (U.S.-Band) ☒ PCS 1900 (U.S.-Band)

Release Version : R99

GPRS Class : Class 12

Uplink : GSM 900: 880MHz ~ 915MHz
DCS 1800: 1710MHz ~ 1785MHz

Downlink : GSM 900: 925MHz ~ 960MHz
DCS 1800: 1805MHz ~ 1880MHz

Type Of Modulation : GMSK for GSM/GPRS;

Antenna Description : Internal Antenna;
1.2dBi (max.) For GSM 850;
1.2dBi (max.) For GSM 900;
1.2dBi (max.) For DCS 1800;
1.2dBi (max.) For PCS 1900

Power Class : GSM 900: Level 5, DCS 1800: Level 0

3G :

Support Band : ☐ WCDMA Band II (U.S.-Band)
☐ WCDMA Band V (U.S.-Band)
☐ WCDMA Band IV (U.S.-Band)
☒ WCDMA Band I (EU-Band)
☒ WCDMA Band VIII (EU-Band)

Release Version : R8

Uplink : WCDMA Band I: 1920MHz ~ 1980MHz
WCDMA Band VIII: 880MHz~915MHz

Downlink : WCDMA Band I: 2110MHz ~ 2170MHz
WCDMA Band VIII: 925MHz~960MHz

Type Of Modulation : WCDMA: BPSK; HSDPA/HSUPA: BPSK

Antenna Description : Internal Antenna;
1.2dBi (max.) For WCDMA Band I;
1.2dBi (max.) For WCDMA Band VIII

Power Class : Level 3

LTE :

Support Band : ☒ E-UTRA Band 1(EU-Band)



	<input checked="" type="checkbox"/> E-UTRA Band 3(EU-Band)
	<input checked="" type="checkbox"/> E-UTRA Band 7(EU-Band)
	<input checked="" type="checkbox"/> E-UTRA Band 8(EU-Band)
	<input checked="" type="checkbox"/> E-UTRA Band 20(EU-Band)
LTE Release Version	: R9
	Uplink: E-UTRA Band 1: 1920MHz ~ 1980MHz
	E-UTRA Band 3: 1710MHz~1785MHz
	E-UTRA Band 7: 2500MHz ~ 2570MHz
	E-UTRA Band 8: 880MHz~815MHz
FDD Band	: E-UTRA Band 20: 832MHz ~ 862MHz
	Downlink: E-UTRA Band 1: 2110MHz ~ 2170MHz
	E-UTRA Band 3: 1805MHz~1880MHz
	E-UTRA Band 7: 2620MHz ~ 2690MHz
	E-UTRA Band 8: 925MHz~960MHz
	E-UTRA Band 20: 791MHz ~ 821MHz
Type Of Modulation	: QPSK/16QAM
	Internal Antenna;
Antenna Description	: 1.2dBi (max.) For E-UTRA Band 1;
	1.2dBi (max.) For E-UTRA Band 3;
	1.2dBi (max.) For E-UTRA Band 7;
	0.7dBi (max.) For E-UTRA Band 8;
	1.2dBi (max.) For E-UTRA Band 20;
Power Class	: Class 3
Bluetooth	:
Frequency Range	: 2402MHz ~ 2480MHz
Channel Number	: 79 channels for Bluetooth V4.1(BDR/EDR)
	40 channels for Bluetooth V4.1(BT LE)
Channel Spacing	: 1MHz for Bluetooth V4.1(BDR/EDR)
	2MHz for Bluetooth V4.1(BT LE)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V4.1(BDR/EDR)
	GFSK for Bluetooth V4.1(BT LE)
Bluetooth Version	: V4.1
Antenna Description	: Internal Antenna, 1.97dBi(Max.)
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz ~ 2472MHz
Channel Spacing	: 5MHz
Channel Number	: 13 Channel for 20MHz bandwidth(2412~2472MHz)
	9 channels for 40MHz bandwidth(2422~2462MHz)
Modulation Type	: 802.11b: DSSS; 802.11g/n: OFDM
Antenna Description	: Internal Antenna, 1.2dBi(Max.)
GPS Receiver	:
Receive Frequency	: 1575.42MHz
Channel Number	: 1





Antenna Description : Internal Antenna, 0dBi(Max.)

LA
S
OY



1.2. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
OPPO	Adapter	OP52KAUH	---	CE

Note: The adapter are only used test, not shipped

1.3. External I/O

I/O Port Description	Quantity	Cable
---	---	---

1.4. Objective

Standard Referenced	Standard Title	Standard Version
ETSI EN 301 908-1	IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU; Part 1: Introduction and common requirements	V11.1.1 (2016-07)
ETSI EN 301 908-2	IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU; Part 2: CDMA Direct Spread (UTRA FDD) User Equipment (UE)	V11.1.2 (2017-08)

The objective is to determine compliance with ETSI EN 301 908-1 V13.1.1 (2019-11) & ETSI EN 301 908-2 V11.1.2 (2017-08).

1.5. Test Conditions

Conditions	Temperature	Voltage
Normal	21-25℃	DC 3.7V
Low extreme Temperature/Low extreme Voltage (TL/VL);	-20℃	DC 3.3V
Low extreme Temperature/High extreme Voltage (TL/VH);	-20℃	DC 4.2V
High extreme Temperature/Low extreme Voltage (TH/VL);	+45℃	DC 3.3V
High extreme Temperature/High extreme Voltage (TH/VH).	+45℃	DC 4.2V
Note1: For all conditions, the humidity range is:40-75%, the pressure range is 86-106kPa.The High Voltage DC 4.2V and Low Voltage DC 3.3V was declared by manufacturer		



1.6. Description Of Test Mode

1. WCDMA Band I

- 1). Low Channel Operation(9612Channel)
- 2). Middle Channel Operation(9750Channel)
- 3). High Channel Operation(9888Channel)

2. WCDMA Band VIII

- 1). Low Channel Operation(2713Channel)
- 2). Middle Channel Operation(2788Channel)
- 3). High Channel Operation(2862Channel)

Note: The EUT has two SIM card slots(SIM1 and SIM2). The result for GSM/WCDMA/LTE card slot(SIM1) is the worst case which was only recorded.

1.7. Measurement Uncertainty (95% confidence levels, k=2)

Test Item		Uncertainty
Radio Frequency	:	0.9×10^{-4}
Total RF Power, Conducted	:	1.0 dB
RF Power Density, Conducted	:	1.8 dB
Spurious Emissions, Conducted	:	1.8 dB
All Emissions, Radiated	:	3.1 dB
Temperature	:	0.5 °C
Humidity	:	1 %
DC And Low Frequency Voltages	:	1 %

1.8. Description of Test Facility

FCC Registration Number is 254912.

Industry Canada Registration Number is 9642A.

EMSD Registration Number is ARCB0108.

UL Registration Number is 100571-492.

TUV SUD Registration Number is SCN1081.

TUV RH Registration Number is UA 50296516-001.

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier: CN0071.



2. SYSTEM TEST CONFIGURATION

2.1. Justification

N/A

2.2. EUT Exercise Software

N/A

2.3. Special Accessories

The special accessories were supplied by Shenzhen LCS Compliance Testing Laboratory Ltd.

2.4. Block Diagram/Schematics

Please refer to the related document.

2.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

2.6. Test Setup

Please refer to the test setup photo.



3. SUMMARY OF TEST RESULTS

Test Engineer	:	Li Huan
Temperature/ Humidity:	:	23.6°C / 54.1%

Reference Clause No. (ETSI EN 301 908-2)	Description of Test Items	WCDMA Band VIII	WCDMA Band I
		Result	Result
4.2.2	Transmitter maximum output power		
	Normal	Pass	Pass
	TL/VL	Pass	Pass
	TL/VH	Pass	Pass
	TH/VL	Pass	Pass
	TH/VH	Pass	Pass
	Transmitter maximum output power for HSDPA & HSUPA		
	Normal	Pass	Pass
	TL/VL	Pass	Pass
	TL/VH	Pass	Pass
	TH/VL	Pass	Pass
	TH/VH	Pass	Pass
4.2.3	Transmitter spectrum emission mask		
	Normal	Pass	Pass
	Transmitter spectrum emission mask for HSDPA & HSUPA		
	Normal	Pass	Pass
4.2.4	Transmitter spurious emissions		
	Normal	Pass	Pass
	Transmitter spurious emission for HSDPA & HSUPA		
	Normal	Pass	Pass
4.2.5	Transmitter minimum output power		
	Normal	Pass	Pass
	TL/VL	Pass	Pass
	TL/VH	Pass	Pass
	TH/VL	Pass	Pass
	TH/VH	Pass	Pass
4.2.6	Receiver Adjacent Channel Selectivity (ACS)		
	NT / NV	Pass	Pass
	Receiver Adjacent Channel Selectivity for HSDPA & HSUPA		
	NT / NV	Pass	Pass
4.2.7	Receiver blocking characteristics		
	Normal	Pass	Pass
4.2.8	Receiver spurious response		
	Normal	Pass	Pass



4.2.9	Receiver intermodulation characteristics		
	Normal	Pass	Pass
4.2.10	Receiver spurious emissions		
	Normal	Pass	Pass
4.2.11	Out-of-synchronization handling of output power		
	Normal	Pass	Pass
4.2.12	Transmitter Adjacent Channel Leakage power Ratio (ACLR)		
	Normal	Pass	Pass
	TL/VL	Pass	Pass
	TL/VH	Pass	Pass
	TH/VL	Pass	Pass
	TH/VH	Pass	Pass
	Transmitter Adjacent Channel Leakage power Ratio (ACLR) for HSDPA & HSUPA		
	Normal	Pass	Pass
	TL/VL	Pass	Pass
	TL/VH	Pass	Pass
	TH/VL	Pass	Pass
	TH/VH	Pass	Pass
4.2.13	Receiver Reference Sensitivity level		
	Normal	Pass	Pass
	TL/VL	Pass	Pass
	TL/VH	Pass	Pass
	TH/VL	Pass	Pass
	TH/VH	Pass	Pass
	Receiver Reference Sensitivity level for HSDPA & HSUPA		
	Normal	Pass	Pass
	TL/VL	Pass	Pass
	TL/VH	Pass	Pass
	TH/VL	Pass	Pass
	TH/VH	Pass	Pass

Reference Clause No. (ETSI EN 301 908-1)	Description of Test Items	WCDMA Band VIII	WCDMA Band I
		Result	Result
4.2.2	Radiated emissions (UE)		
	Normal	Pass	Pass
4.2.4	Control and monitoring functions (UE)		
	Normal	Pass	Pass

***Note:

Result: Describes test result of Test Case.

Pass: Test Case passed on specified conformance test platform.

Normal(TN/VN): Normal temperature – 25°C; Normal voltage. – DC 3.7V

TH: High extreme Temperature – +45°C

VH: High extreme Voltage – DC 4.2V

TL: Low extreme Temperature – -20°C



VL: Low extreme Voltage – DC 3.3V

N/A: Not applicable.

—: Not test.

4. LIST OF MEASURING EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	LTE Test Software	Tonscend	JS1120-1	N/A	N/A	N/A
2	RF Control Unit	Tonscend	JS0806	158060009	2020-06-10	2021-06-09
3	MXA Signal Analyzer	Agilent	N9020A	MY51250905	2019-11-14	2020-11-13
4	DC Power Supply	Agilent	E3642A	N/A	2019-11-14	2020-11-13
5	MXG Vector Signal Generator	Agilent	N5182A	MY47071151	2020-06-10	2021-06-09
6	PSG Analog Signal Generator	Agilent	E8257D	MY4520521	2020-06-10	2021-06-09
7	Temperature & Humidity Chamber	GUANGZHOU GOGNWN	GDS-100	70932	2019-10-09	2020-10-08
8	EMI Test Software	EZ	EZ-EMC	/	N/A	N/A
9	3m Fully Anechoic Chamber	MRDIANZI	FAC-3M	MR009	2019-09-27	2020-09-26
10	Positioning Controller	MF	MF-7082	/	2020-06-11	2021-06-10
11	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2019-07-25	2020-07-24
12	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2019-07-25	2020-07-24
13	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2020-06-30	2021-06-29
14	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2019-09-19	2020-09-18
15	Broadband Preamplifier	SCHWARZBECK	BBV 9719	9719-025	2019-09-19	2020-09-18
16	EMI Test Receiver	R&S	ESR 7	101181	2020-06-11	2021-06-10
17	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2019-11-14	2020-11-13
18	Broadband Preamplifier	phx	BP-01M18G	P190501	2020-06-30	2021-06-29
19	RF Cable-R03m	Jye Bao	RG142	CB021	2020-06-11	2021-06-10
20	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2020-06-11	2021-06-10
21	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW 500	103818	2020-06-10	2021-06-09
22	RF Filter	Micro-Tronics	BRC50718	S/N-017	2020-06-10	2021-06-09
23	RF Filter	Micro-Tronics	BRC50719	S/N-011	2020-06-10	2021-06-09
24	RF Filter	Micro-Tronics	BRC50720	S/N-011	2020-06-10	2021-06-09
25	RF Filter	Micro-Tronics	BRC50721	S/N-013	2020-06-10	2021-06-09
26	RF Filter	Micro-Tronics	BRM50702	S/N-195	2020-06-10	2021-06-09
27	6dB Attenuator	/	100W/6dB	1172040	2020-06-10	2021-06-09
28	3dB Attenuator	/	2N-3dB	/	2020-06-10	2021-06-09
29	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2019-11-14	2020-11-13

Note: All equipment is calibrated through CHINA CEPREI LABORATORY and GUANGZHOU LISAI CALIBRATION AND TEST CO., LTD.



5. PHOTOGRAPHS OF TEST SETUP

Please refer to separated files Appendix D for Photographs of Test Setup_RF.

6. PHOTOGRAPHS OF THE EUT

Please refer to separated files Appendix C for Photographs of The EUT.



Annex A

Transmitter maximum output power

The worst test result of maximum output power for WCDMA Band I

Test Condition		Measure Result (dBm)			Nominal Output Power (dBm)	Conclusion
Temperature (°C)	Voltage (Vdc)	Low Channel 9612	Middle Channel 9750	High Channel 9888		
-20	DC 3.3V	22.28	22.28	22.23	24	Pass
	DC 3.7V	22.01	21.99	22.03		Pass
	DC 4.2V	21.76	21.75	21.71		Pass
25	DC 3.3V	22.72	22.80	22.74		Pass
	DC 3.7V	22.15	22.12	22.18		Pass
	DC 4.2V	22.21	22.17	22.24		Pass
45	DC 3.3V	21.92	21.83	21.81		Pass
	DC 3.7V	21.65	21.58	21.61		Pass
	DC 4.2V	21.78	21.77	21.83		Pass

The worst test result of maximum output power for WCDMA Band I (HSUPA)

Test Condition		Measure Result (dBm)			Nominal Output Power (dBm)	Conclusion
Temperature (°C)	Voltage (Vdc)	Low Channel 9612	Middle Channel 9750	High Channel 9888		
-20	DC 3.3V	22.32	22.29	22.20	24	Pass
	DC 3.7V	22.09	22.05	22.01		Pass
	DC 4.2V	21.78	21.77	21.79		Pass
25	DC 3.3V	22.59	22.62	22.67		Pass
	DC 3.7V	22.13	22.04	22.01		Pass
	DC 4.2V	22.31	22.32	22.38		Pass
45	DC 3.3V	21.92	21.91	21.94		Pass
	DC 3.7V	21.62	21.56	21.53		Pass
	DC 4.2V	21.82	21.78	21.69		Pass

The worst test result of maximum output power for WCDMA Band I (HSDPA)

Test Condition		Measure Result (dBm)			Nominal Output Power (dBm)	Conclusion
Temperature (°C)	Voltage (Vdc)	Low Channel 9612	Middle Channel 9750	High Channel 9888		
-20	DC 3.3V	22.27	22.35	22.42	24	Pass
	DC 3.7V	22.03	21.99	21.97		Pass
	DC 4.2V	21.79	21.71	21.75		Pass
25	DC 3.3V	22.67	22.66	22.66		Pass
	DC 3.7V	22.19	22.24	22.24		Pass
	DC 4.2V	22.21	22.11	22.20		Pass
45	DC 3.3V	21.87	21.84	21.83		Pass
	DC 3.7V	21.57	21.62	21.66		Pass
	DC 4.2V	21.81	21.80	21.81		Pass



The worst test result of maximum output power for WCDMA Band VIII

Test Condition		Measure Result (dBm)			Nominal Output Power (dBm)	Conclusion
Temperature (°C)	Voltage (Vdc)	Low Channel 2713	Middle Channel 2788	High Channel 2862		
-20	DC 3.3V	22.31	22.34	22.32	24	Pass
	DC 3.7V	22.04	22.05	22.12		Pass
	DC 4.2V	21.68	21.69	21.74		Pass
25	DC 3.3V	22.70	22.73	22.76		Pass
	DC 3.7V	22.24	22.21	22.25		Pass
	DC 4.2V	22.22	22.18	22.12		Pass
45	DC 3.3V	21.92	21.96	21.99		Pass
	DC 3.7V	21.71	21.78	21.78		Pass
	DC 4.2V	21.80	21.75	21.80		Pass

The worst test result of maximum output power for WCDMA Band VIII (HSUPA)

Test Condition		Measure Result (dBm)			Nominal Output Power (dBm)	Conclusion
Temperature (°C)	Voltage (Vdc)	Low Channel 2713	Middle Channel 2788	High Channel 2862		
-20	DC 3.3V	22.37	22.37	22.37	24	Pass
	DC 3.7V	22.04	22.02	22.01		Pass
	DC 4.2V	21.76	21.67	21.63		Pass
25	DC 3.3V	22.64	22.68	22.67		Pass
	DC 3.7V	22.20	22.18	22.23		Pass
	DC 4.2V	22.21	22.27	22.20		Pass
45	DC 3.3V	21.94	21.88	21.93		Pass
	DC 3.7V	21.69	21.67	21.68		Pass
	DC 4.2V	21.83	21.89	21.86		Pass

The worst test result of maximum output power for WCDMA Band VIII (HSDPA)


Test Condition		Measure Result (dBm)			Nominal Output Power (dBm)	Conclusion
Temperature (°C)	Voltage (Vdc)	Low Channel 2713	Middle Channel 2788	High Channel 2862		
-20	DC 3.3V	22.31	22.31	22.22	24	Pass
	DC 3.7V	22.01	22.00	22.06		Pass
	DC 4.2V	21.79	21.76	21.81		Pass
25	DC 3.3V	22.73	22.69	22.70		Pass
	DC 3.7V	22.19	22.23	22.19		Pass
	DC 4.2V	22.28	22.29	22.34		Pass
45	DC 3.3V	21.96	22.04	22.03		Pass
	DC 3.7V	21.68	21.65	21.61		Pass
	DC 4.2V	21.77	21.79	21.71		Pass




Transmitter spurious emissions

(Note: Only Record The Worst Test Result.)


The Worst Test Result of Spurious Emissions for Band I (Middle Channel, Traffic)




9KHz~150KHz




150KHz~30MHz




30MHz~1GHz



1GHz~1.9375GHz




1.9630GHz~12.75GHz




791MHz~821MHz




The Worst Test Result of Spurious Emissions for Band I (Middle Channel, Traffic)




The Worst Test Result of Spurious Emissions for Band VIII (Middle Channel, Traffic)




9KHz~150KHz




150KHz~30MHz




30MHz~885.1MHz



910.1MHz~1GHz




1GHz~12.75GHz




791MHz~821MHz


The Worst Test Result of Spurious Emissions for Band VIII (Middle Channel, Traffic)




925MHz~935MHz




935MHz~960MHz




1805MHz~1830MHz



1830MHz~1880MHz




2.110GHz~2.170GHz



2.585GHz~2.640GHz



The Worst Test Result of Spurious Emissions for Band VIII (Middle Channel, Traffic)





Transmitter spurious emissions

Radiated spurious emissions - MS allocated a channel(Worst Case)

WCDMA Band I: Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
54.02	Horizontal	-78.20	-36.00	Pass
936.85	H	-80.95	-36.00	
3821.01	H	-60.71	-30.00	
5732.03	H	-58.63	-30.00	
7642.08	H	-54.25	-30.00	
WCDMA Band I: Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.71	Vertical	-77.96	-36.00	Pass
965.57	V	-71.34	-36.00	
3820.19	V	-66.41	-30.00	
5735.15	V	-60.99	-30.00	
7640.91	V	-55.07	-30.00	

WCDMA Band VIII: Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.35	Horizontal	-71.38	-36.00	Pass
979.20	H	-78.23	-36.00	
1281.27	H	-62.38	-30.00	
2583.26	H	-54.85	-30.00	
3505.48	H	-56.61	-30.00	
WCDMA Band VIII: Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.78	Vertical	-72.15	-36.00	Pass
991.63	V	-72.01	-36.00	
1280.23	V	-67.92	-30.00	
2584.94	V	-59.18	-30.00	
3502.29	V	-52.57	-30.00	



Radiated spurious emissions - MS in Idle Mode(Worst Case)

WCDMA Band I: Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.51	Horizontal	-73.67	-57.00	Pass
773.63	H	-79.42	-57.00	
1791.23	H	-61.54	-47.00	
2702.46	H	-57.59	-47.00	
3611.84	H	-55.01	-47.00	
WCDMA Band I: Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.77	Vertical	-76.86	-57.00	Pass
990.22	V	-78.70	-57.00	
1795.58	V	-64.78	-47.00	
2704.82	V	-59.03	-47.00	
3610.60	V	-52.34	-47.00	

WCDMA Band VIII: Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.37	Horizontal	-72.59	-57.00	Pass
851.48	H	-80.27	-57.00	
1699.55	H	-60.32	-47.00	
2679.11	H	-57.31	-47.00	
3241.03	H	-55.58	-47.00	
WCDMA Band VIII: Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.90	Vertical	-71.49	-57.00	Pass
877.37	V	-75.13	-57.00	
1700.22	V	-67.17	-47.00	
2679.79	V	-51.92	-47.00	
3240.49	V	-52.48	-47.00	

-----THE END OF REPORT-----