



RADIO TEST REPORT

For

myFirst Tech Asia Pte. Ltd.

myFirst Fone R1s、myFirst Fone R1c

Test Model: KW1305

Additional Model No.: myFirst Fone R

Prepared for : myFirst Tech Asia Pte. Ltd.
Address : 31 Woodlands Close, #01-22 Woodlands Horizon Singapore 737855

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : November 25, 2023
Number of tested samples : 2
Serial number : Prototype
Date of Test : November 25, 2023 ~ January 05, 2024
Date of Report : January 06, 2024



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
Tel: (+86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



RADIO TEST REPORT	
ETSI EN 301 908-1 V13.1.1 (2019-11) & ETSI EN 301 908-13 V13.2.1 (2022-02)	
Report Reference No.	LCSA11253005EH
Date of Issue	January 06, 2024
Testing Laboratory Name	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
Testing Location/ Procedure	Full application of Harmonised standards <input checked="" type="checkbox"/> Partial application of Harmonised standards <input type="checkbox"/> Other standard testing method <input type="checkbox"/>
Applicant's Name	myFirst Tech Asia Pte. Ltd.
Address	31 Woodlands Close, #01-22 Woodlands Horizon Singapore 737855
Test Specification	
Standard	ETSI EN 301 908-1 V13.1.1 (2019-11) ETSI EN 301 908-13 V13.2.1 (2022-02)
Test Report Form No.	LCSEMC-1.0
TRF Originator	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF	Dated 2017-06
Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test Item Description	
myFirst Fone R1s、 myFirst Fone R1c	
Trade Mark	myFirst
Test Model	KW1305
Ratings	Input: 5V=1A Battery: DC 3.8V, 605mAh
Result	Positive

Compiled by:

Li Huan/ Administrator

Supervised by:

Cary Luo/ Technique principal

Approved by:

Gavin Liang/ Manager



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



RADIO -- TEST REPORT

Test Report No. : LCSA11253005EH	January 06, 2024 Date of issue
----------------------------------	-----------------------------------

Test Model.....	: KW1305
EUT.....	: myFirst Fone R1s、myFirst Fone R1c
Applicant.....	: myFirst Tech Asia Pte. Ltd.
Address.....	: 31 Woodlands Close,#01-22Woodlands Horizon Singapore 737855
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: myFirst Tech Asia Pte. Ltd.
Address.....	: 31 Woodlands Close,#01-22Woodlands Horizon Singapore 737855
Telephone.....	: /
Fax.....	: /
Factory.....	: UMEOX Innovations Co.,Ltd
Address.....	: Room 08-09, Floor 12, KeYan Bldg, Tsinghua High Tech Park, XinDong Road 1, NanShan, Shenzhen, China
Telephone.....	: /
Fax.....	: /

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Report Version	Issue Date	Revision Content	Revised By
000	January 06, 2024	Initial Issue	---



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street,
Bao'an District, Shenzhen, Guangdong, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



TABLE OF CONTENTS

1. GENERAL INFORMATION	6
1.1. PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2. SUPPORT EQUIPMENT LIST	9
1.3. EXTERNAL I/O	9
1.4. OBJECTIVE	9
1.5. TEST CONDITIONS	9
1.6. DESCRIPTION OF TEST MODE	10
1.7. MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	10
1.8. DESCRIPTION OF TEST FACILITY	10
2. SYSTEM TEST CONFIGURATION	11
2.1. JUSTIFICATION	11
2.2. EUT EXERCISE SOFTWARE	11
2.3. SPECIAL ACCESSORIES	11
2.4. BLOCK DIAGRAM/SCHEMATICS	11
2.5. EQUIPMENT MODIFICATIONS	11
2.6. TEST SETUP	11
3. SUMMARY OF TEST RESULTS	12
4. LIST OF MEASURING EQUIPMENT	14
5. PHOTOGRAPHS OF TEST SETUP	15
6. PHOTOGRAPHS OF THE EUT	15





1. GENERAL INFORMATION

1.1. Product Description for Equipment Under Test (EUT)

EUT	: myFirst Fone R1s、myFirst Fone R1c
Test Model	: KW1305
Additional Model No.	: myFirst Fone R
Model Declaration	: PCB board, structure and internal of these model(s) are the same, : So no additional models were tested
Power Supply	: Input: 5V $\overline{=}$ 1A Battery: DC 3.8V, 605mAh
Hardware Version	: S11N-MB-V2.0
Software Version	: /
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V4.2 (BDR/EDR) 40 channels for Bluetooth V4.2 (BT LE)
Channel Spacing	: 1MHz for Bluetooth V4.2 (BDR/EDR) 2MHz for Bluetooth V4.2 (BT LE)
Modulation Type	: GFSK, $\pi/4$ -DQPSK for Bluetooth V4.2 (BDR/EDR) GFSK for Bluetooth V4.2 (BT LE)
Bluetooth Version	: V4.2
Antenna Description	: LDS Antenna, -0.2dBi(Max.)
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2472MHz
Channel Spacing	: 5MHz
Channel Number	: 13 Channel for 20MHz bandwidth(2412~2472MHz)
Modulation Type	: 802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: LDS Antenna, -0.2dBi(Max.)
2G	:
Support Band	: <input checked="" type="checkbox"/> GSM 900 (EU-Band) <input checked="" type="checkbox"/> DCS 1800 (EU-Band) <input type="checkbox"/> GSM 850 (U.S.-Band) <input type="checkbox"/> PCS 1900 (U.S.-Band)
Release Version	: R99
GPRS Class	: Class 12
EGPRS Class	: Class 12
Uplink	: GSM 900: 880MHz~915MHz DCS 1800: 1710MHz~1785MHz



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Downlink : GSM 900: 925MHz~960MHz
DCS 1800: 1805MHz~1880MHz
Type Of Modulation : GMSK for GSM/GPRS; GMSK/8PSK for EGPRS
Antenna Description : LDS Antenna
-3.2dBi (max.) For GSM 900
-0.7dBi (max.) For DCS 1800
Power Class : GSM 900: Level 5, DCS 1800: Level 0
EGPRS 900: Level 8, EGPRS 1800: Level 2

3G :

Support Band : ☐ WCDMA Band II (U.S.-Band)
☐ WCDMA Band V (U.S.-Band)
☐ WCDMA Band IV (U.S.-Band)
☒ WCDMA Band I (EU-Band)
☒ WCDMA Band VIII (EU-Band)
Release Version : R9
Uplink : WCDMA Band I: 1920MHz~1980MHz
WCDMA Band VIII: 880MHz~915MHz
Downlink : WCDMA Band I: 2110MHz~2170MHz
WCDMA Band VIII: 925MHz~960MHz
Type Of Modulation : QPSK/16QAM
Antenna Description : LDS Antenna
-0.6dBi (max.) For WCDMA Band I
-3.2dBi (max.) For WCDMA Band VIII
Power Class : Level 3

LTE :

Support Band : ☒ E-UTRA Band 1(EU-Band)
☒ E-UTRA Band 3(EU-Band)
☒ E-UTRA Band 7(EU-Band)
☒ E-UTRA Band 8(EU-Band)
☒ E-UTRA Band 20(EU-Band)
☒ E-UTRA Band 28(EU-Band)
☒ E-UTRA Band 38(EU-Band)
LTE Release Version : R12
FDD Band : Uplink: E-UTRA Band 1: 1920MHz~1980MHz
E-UTRA Band 3: 1710MHz~1785MHz
E-UTRA Band 7: 2500MHz~2570MHz
E-UTRA Band 8: 880MHz~915MHz
E-UTRA Band 20: 832MHz~862MHz
E-UTRA Band 28: 703MHz~748MHz
Downlink: E-UTRA Band 1: 2110MHz~2170MHz
E-UTRA Band 3: 1805MHz~1880MHz
E-UTRA Band 7: 2620MHz~2690MHz



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



E-UTRA Band 8: 925MHz~960MHz
E-UTRA Band 20: 791MHz~821MHz
E-UTRA Band 28: 758MHz~803MHz
TDD Band : E-UTRA Band 38: 2570MHz ~ 2620MHz
Type Of Modulation : QPSK/16QAM
Antenna Description : LDS Antenna
-0.5dBi (max.) For E-UTRA Band 1
-0.7dBi (max.) For E-UTRA Band 3
-0.2dBi (max.) For E-UTRA Band 7
-3.2dBi (max.) For E-UTRA Band 8
-2.5dBi (max.) For E-UTRA Band 20
-3.5dBi (max.) For E-UTRA Band 28
-0.2dBi (max.) For E-UTRA Band 38
Power Class : Class 3
GPS Receiver :
Receive Frequency : 1575.42MHz
Channel Number : 1
Antenna Description : LDS Antenna, -0.9dBi(Max.)
GLONASS Receiver :
Receive Frequency : 1602.5625MHz
Channel Number : 1
Antenna Description : LDS Antenna, -0.9dBi(Max.)





1.2. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
ShenZhen BaiJunda Electronic Co., Ltd.	Power Adapter	UT-580S-5100UY	---	CE

Note: The adapter is supplied by lab and only use tested.

1.3. External I/O

I/O Port Description	Quantity	Cable
Power Port	1	USB Cable: 1.0m, unshielded

1.4. Objective

Standard Referenced	Standard Title	Standard Version
ETSI EN 301 908-1	IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 1: Introduction and common requirements; Release 15	V15.2.1 (2023-01)
ETSI EN 301 908-13	IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 13: Evolved Universal Terrestrial Radio Access (E-UTRA) User Equipment (UE)	V13.2.1 (2022-02)
ETSI TS 136 521-1	LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Conformance testing (3GPP TS 36.521-1 version 16.9.0 Release 16)	V16.9.0 (2021-03)

The objective is to determine compliance with ETSI EN 301 908-1 V13.1.1 (2019-11) & ETSI EN 301 908-13 V13.2.1 (2022-02).

1.5. Test Conditions

Conditions	Temperature	Voltage
Normal	21-25°C	DC 3.8V
Low extreme Temperature/Low extreme Voltage (TL/VL);	-20°C	DC 3.4V
Low extreme Temperature/High extreme Voltage (TL/VH);	-20°C	DC 4.2V
High extreme Temperature/Low extreme Voltage (TH/VL);	45°C	DC 3.4V
High extreme Temperature/High extreme Voltage (TH/VH).	45°C	DC 4.2V

Note1: For all conditions, the humidity range is: 40-75%, the pressure range is 86-106kPa. The High Voltage DC 4.2V and Low Voltage DC 3.4V was declared by manufacturer



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



1.6. Description Of Test Mode

The following operating modes were applied for the related test items. For radiated measurement, the test was performed with EUT in X, Y, Z position and the worse case was found when EUT in Y position. All test modes were tested, only the result of the worst case was recorded in the report.

Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
	1.4	3	5	10	15	20	QPSK	16QAM	1	Part	Full	L	M	H
1	N/A	N/A	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y
3	Y	/	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y
7	N/A	N/A	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y
8	Y	/	Y	Y	N/A	N/A	Y	Y	Y	Y	Y	Y	Y	Y
20	N/A	N/A	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y
28	N/A	Y	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y
38	N/A	N/A	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y

Note:

- 1)The mark “Y” means that this configuration is chosen for testing.
- 2)The mark “/” means that this bandwidth is supported but is not chosen for testing.
- 3)The mark “N/A” means that this bandwidth is not supported.

1.7. Measurement Uncertainty (95% confidence levels, k=2)

Test Item	Uncertainty
Radio Frequency	0.9×10^{-4}
Total RF Power, Conducted	1.0 dB
RF Power Density, Conducted	1.8 dB
Spurious Emissions, Conducted	1.8 dB
All Emissions, Radiated	3.1 dB
Temperature	0.5°C
Humidity	1 %
DC And Low Frequency Voltages	1 %

1.8. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



2. SYSTEM TEST CONFIGURATION

2.1. Justification

N/A

2.2. EUT Exercise Software

N/A

2.3. Special Accessories

The special accessories were supplied by Shenzhen LCS Compliance Testing Laboratory Ltd.

2.4. Block Diagram/Schematics

Please refer to the related document.

2.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

2.6. Test Setup

Please refer to the test setup photo.





3. SUMMARY OF TEST RESULTS

Test Engineer	:	Taylor Hu
Temperature/ Humidity:	:	22.7°C/ 51.3%

Reference Clause No. (ETSI EN 301 908-13)	Description of Test Items	Result					
		E-UTRA Band					
		Band 1	Band 3	Band 7	Band 8	Band 20	Band 28
4.2.2	Transmitter Maximum Output Power						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VH	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VH	Pass	Pass	Pass	Pass	Pass	Pass
4.2.5	Transmitter Minimum Output Power						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VH	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VH	Pass	Pass	Pass	Pass	Pass	Pass
4.2.3	Transmitter Spectrum Emission Mask						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.11	Transmitter Adjacent Channel Leakage Power Ratio						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VH	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VH	Pass	Pass	Pass	Pass	Pass	Pass
4.2.4	Transmitter Spurious Emissions						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.10	Receiver Spurious Emissions						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.6	Receiver Adjacent Channel Selectivity (ACS)						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.7	Receiver Blocking Characteristics						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.8	Receiver Spurious Response						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.9	Receiver Intermodulation Characteristics						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass





4.2.12	Receiver Reference Sensitivity Level						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TL/VH	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VL	Pass	Pass	Pass	Pass	Pass	Pass
	TH/VH	Pass	Pass	Pass	Pass	Pass	Pass

Reference Clause No. (ETSI EN 301 908-1)	Description of Test Items	Result					
		E-UTRA Band					
		Band 1	Band 3	Band 7	Band 8	Band 20	Band 28
4.2.2	Radiated emissions (UE)						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass
4.2.4	Control and monitoring functions (UE)						
	Normal	Pass	Pass	Pass	Pass	Pass	Pass

***Note:

Result: Describes test result of Test Case.

Pass: Test Case passed on specified conformance test platform.

Normal(TN/VN): Normal temperature – 25°C; Normal voltage. – DC 3.8V

TH: High extreme Temperature – +45°C

VH: High extreme Voltage – DC 4.2V

TL: Low extreme Temperature – -20°C

VL: Low extreme Voltage – DC 3.4V

N/A: Not applicable.

—: Not test.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



4. LIST OF MEASURING EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	LTE Test Software	Tonscend	JS1120-1	N/A	N/A	N/A
2	RF Control Unit	Tonscend	JS0806-1	158060009	2023-10-18	2024-10-17
3	MXA Signal Analyzer	Agilent	N9020A	MY51250905	2023-10-18	2024-10-17
4	DC Power Supply	Agilent	E3642A	N/A	2023-10-18	2024-10-17
5	MXG Vector Signal Generator	Agilent	N5182A	MY47071151	2023-06-09	2024-06-08
6	PSG Analog Signal Generator	Agilent	E8257D	MY4520521	2023-06-09	2024-06-08
7	Temperature & Humidity Chamber	GUANGZHOU GOGNWEN	GDS-100	70932	2023-10-05	2024-10-04
8	EMI Test Software	Farad	EZ	/	N/A	N/A
9	3m Full Anechoic Chamber	MRDIANZI	FAC-3M	MR009	2022-08-17	2025-08-16
10	Positioning Controller	Max-Full	MF7802BS	MF780208586	N/A	N/A
11	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2021-08-29	2024-08-28
12	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2021-09-12	2024-09-11
13	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2021-09-05	2024-09-04
14	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2021-08-29	2024-08-28
15	Broadband Preamplifier	SCHWARZBECK	BBV9719	9719-025	2021-08-29	2024-08-28
16	EMI Test Receiver	R&S	ESR 7	101181	2023-08-15	2024-08-14
17	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2023-07-17	2024-07-16
18	Low-frequency amplifier	SchwarzZBECK	BBV9745	00253	2023-10-18	2024-10-17
19	High-frequency amplifier	JS Denki Pte	PA0118-43	JSPA21009	2023-10-18	2024-10-17
20	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW 500	103818	2023-06-09	2024-06-08
21	RF Filter	Micro-Tronics	BRC50718	017	2023-10-18	2024-10-17
22	RF Filter	Micro-Tronics	BRC50719	011	2023-10-18	2024-10-17
23	RF Filter	Micro-Tronics	BRC50720	011	2023-10-18	2024-10-17
24	RF Filter	Micro-Tronics	BRC50721	013	2023-10-18	2024-10-17
25	RF Filter	Micro-Tronics	BRM50702	195	2023-08-15	2024-08-14
26	6dB Attenuator	/	100W/6dB	1172040	2023-06-09	2024-06-08
27	3dB Attenuator	/	2N-3dB	/	2023-10-18	2024-10-17





5. PHOTOGRAPHS OF TEST SETUP

Please refer to separated files Appendix D for Photographs of Test Setup_RF.

6. PHOTOGRAPHS OF THE EUT

Please refer to separated files Appendix C for Photographs of The EUT.





Annex A

Transmitter maximum output power

The Conducted Power Measurement Result for LTE Band					
Test Result for LTE Band 1					
Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Limit (dBm)
		RB Size	RB Offset		
5MHz	Low Range	1	1RB#0	23.04	20.3~25.7
			8RB#0	22.92	20.3~25.7
	Mid Range	1	1RB#0	23.05	20.3~25.7
			8RB#0	23.07	20.3~25.7
	High Range	1	1RB#24	23.26	20.3~25.7
			8RB#17	23.05	20.3~25.7
20MHz	Low Range	1	1RB#0	23.29	20.3~25.7
			18RB#0	23.11	20.3~25.7
	Mid Range	1	1RB#0	23.29	20.3~25.7
			18RB#0	23.22	20.3~25.7
	High Range	1	1RB#99	23.31	20.3~25.7
			18RB#82	23.26	20.3~25.7

The Conducted Power Measurement Result for LTE Band					
Test Result for LTE Band 3					
Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Limit (dBm)
		RB Size	RB Offset		
1.4MHz	Low Range	1	1RB#0	23.54	20.3~25.7
	Mid Range	1	1RB#0	23.39	20.3~25.7
	High Range	1	1RB#0	23.59	20.3~25.7
			5RB#0	23.61	20.3~25.7
5MHz	Low Range	1	1RB#0	23.56	20.3~25.7
			1RB#24	23.61	20.3~25.7
	Mid Range	1	1RB#0	23.51	20.3~25.7
			1RB#24	23.53	20.3~25.7
	High Range	1	1RB#0	23.56	20.3~25.7
			1RB#24	23.64	20.3~25.7
20MHz	Low Range	1	8RB#0	23.67	20.3~25.7
			1RB#0	23.63	20.3~25.7
	Mid Range	1	1RB#99	23.50	20.3~25.7
			1RB#0	23.79	20.3~25.7
	High Range	1	1RB#99	23.65	20.3~25.7
			1RB#0	23.72	20.3~25.7
			1RB#99	23.70	20.3~25.7
			18RB#0	23.48	20.3~25.7



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



The Conducted Power Measurement Result for LTE Band

Test Result for LTE Band 7

Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Limit (dBm)
		RB Size	RB Offset		
5MHz	Low Range	1	1RB#0	22.45	20.3~25.7
			1RB#24	22.55	20.3~25.7
	Mid Range	1	1RB#0	22.82	20.3~25.7
			1RB#24	22.79	20.3~25.7
	High Range	1	1RB#0	22.60	20.3~25.7
			1RB#24	22.60	20.3~25.7
20MHz	Low Range	1	1RB#0	22.54	20.3~25.7
			1RB#99	22.79	20.3~25.7
	Mid Range	1	1RB#0	22.67	20.3~25.7
			1RB#99	22.73	20.3~25.7
	High Range	1	1RB#0	22.85	20.3~25.7
			1RB#99	22.73	20.3~25.7
			18RB#0	22.92	20.3~25.7

The Conducted Power Measurement Result for LTE Band

Test Result for LTE Band 8

Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Limit (dBm)
		RB Size	RB Offset		
1.4MHz	Low Range	1	1RB#0	24.03	20.3~25.7
	Mid Range	1	1RB#0	23.55	20.3~25.7
	High Range	1	1RB#0	24.21	20.3~25.7
			5RB#0	24.26	20.3~25.7
5MHz	Low Range	1	1RB#0	24.08	20.3~25.7
			1RB#24	24.21	20.3~25.7
	Mid Range	1	1RB#0	23.81	20.3~25.7
			1RB#24	23.70	20.3~25.7
	High Range	1	1RB#0	24.22	20.3~25.7
			1RB#24	24.09	20.3~25.7
10MHz	Low Range	1	1RB#0	24.03	20.3~25.7
			1RB#49	24.29	20.3~25.7
	Mid Range	1	1RB#0	24.07	20.3~25.7
			1RB#49	23.73	20.3~25.7
	High Range	1	1RB#0	24.08	20.3~25.7
			1RB#49	24.03	20.3~25.7
			12RB#0	24.41	20.3~25.7



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



The Conducted Power Measurement Result for LTE Band

Test Result for LTE Band 20

Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Limit (dBm)
		RB Size	RB Offset		
5MHz	Low Range	1	1RB#0	24.14	20.3~25.7
			1RB#24	24.32	20.3~25.7
	Mid Range	1	1RB#0	23.68	20.3~25.7
			1RB#24	23.59	20.3~25.7
	High Range	1	1RB#0	24.20	20.3~25.7
			1RB#24	23.94	20.3~25.7
20MHz	Low Range	1	1RB#0	24.12	20.3~25.7
			8RB#0	24.12	20.3~25.7
	Mid Range	1	1RB#0	24.34	20.3~25.7
			1RB#99	24.25	20.3~25.7
			1RB#0	24.32	20.3~25.7
			1RB#99	23.77	20.3~25.7
	High Range	1	1RB#0	24.43	20.3~25.7
			1RB#99	24.05	20.3~25.7
			18RB#0	24.09	20.3~25.7
			18RB#0	24.09	20.3~25.7

The Conducted Power Measurement Result for LTE Band

Test Result for LTE Band 28

Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Limit (dBm)
		RB Size	RB Offset		
3MHz	Low Range	1	1RB#0	23.91	20.3~25.7
	Mid Range	1	4RB#0	24.10	20.3~25.7
	High Range	1	1RB#0	24.00	20.3~25.7
			4RB#0	24.08	20.3~25.7
5MHz	Low Range	1	1RB#14	23.55	20.3~25.7
			4RB#11	23.62	20.3~25.7
	Mid Range	1	1RB#0	23.95	20.3~25.7
			8RB#0	23.92	20.3~25.7
	High Range	1	1RB#0	24.04	20.3~25.7
			8RB#0	23.99	20.3~25.7
20MHz	Low Range	1	1RB#24	23.78	20.3~25.7
			8RB#17	23.82	20.3~25.7
	Mid Range	1	1RB#0	24.10	20.3~25.7
			18RB#0	24.14	20.3~25.7
	High Range	1	1RB#0	23.98	20.3~25.7
			18RB#0	24.23	20.3~25.7
			1RB#99	23.89	20.3~25.7
			18RB#82	23.81	20.3~25.7



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



The Conducted Power Measurement Result for LTE Band

Test Result for LTE Band 38

Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Limit (dBm)
		RB Size	RB Offset		
5MHz	Low Range	1	1RB#0	22.91	20.3~25.7
			8RB#0	22.91	20.3~25.7
	Mid Range	1	1RB#0	22.64	20.3~25.7
			8RB#0	22.63	20.3~25.7
	High Range	1	1RB#24	22.81	20.3~25.7
			8RB#17	22.77	20.3~25.7
20MHz	Low Range	1	1RB#0	22.86	20.3~25.7
			18RB#0	22.81	20.3~25.7
	Mid Range	1	1RB#0	22.49	20.3~25.7
			18RB#0	22.81	20.3~25.7
	High Range	1	1RB#99	22.82	20.3~25.7
			18RB#82	22.92	20.3~25.7



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Annex of Radiated spurious emission

Radiated spurious emissions - MS allocated a channel(Worst Case)

LTE Band 1(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.81	Horizontal	-70.64	-36.00	Pass
740.27	H	-74.55	-36.00	
3904.27	H	-68.80	-30.00	
5852.43	H	-56.07	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.12	Vertical	-72.61	-36.00	Pass
794.79	V	-77.06	-36.00	
3903.98	V	-65.94	-30.00	
5850.35	V	-55.96	-30.00	

LTE Band 1(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.24	Horizontal	-72.90	-36.00	Pass
870.36	H	-72.72	-36.00	
3902.23	H	-68.75	-30.00	
5851.56	H	-59.70	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.24	Vertical	-79.13	-36.00	Pass
747.64	V	-78.52	-36.00	
3902.98	V	-68.76	-30.00	
5853.88	V	-56.67	-30.00	





LTE Band 1(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.09	Horizontal	-80.87	-36.00	Pass
784.35	H	-78.55	-36.00	
3902.38	H	-69.97	-30.00	
5850.86	H	-56.81	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.73	Vertical	-77.79	-36.00	Pass
785.47	V	-78.43	-36.00	
3905.87	V	-69.54	-30.00	
5850.46	V	-60.24	-30.00	

LTE Band 1(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.99	Horizontal	-75.69	-36.00	Pass
848.43	H	-71.38	-36.00	
3901.24	H	-66.42	-30.00	
5853.51	H	-55.55	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.25	Vertical	-76.10	-36.00	Pass
988.18	V	-73.13	-36.00	
3901.89	V	-65.23	-30.00	
5852.68	V	-59.19	-30.00	





LTE Band 3(1.4MHz, RB allocation=6): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.79	Horizontal	-71.09	-36.00	Pass
877.73	H	-76.94	-36.00	
3502.41	H	-62.58	-30.00	
5252.67	H	-53.22	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.16	Vertical	-77.07	-36.00	Pass
898.58	V	-71.41	-36.00	
3502.60	V	-63.16	-30.00	
5255.81	V	-58.13	-30.00	

LTE Band 3(1.4MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.61	Horizontal	-72.65	-36.00	Pass
782.90	H	-78.28	-36.00	
3504.92	H	-67.62	-30.00	
5255.64	H	-58.73	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.71	Vertical	-75.28	-36.00	Pass
934.81	V	-71.13	-36.00	
3502.84	V	-65.34	-30.00	
5252.69	V	-56.13	-30.00	





LTE Band 3(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.45	Horizontal	-75.64	-36.00	Pass
834.26	H	-75.16	-36.00	
3504.21	H	-67.92	-30.00	
5254.64	H	-60.73	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.51	Vertical	-73.69	-36.00	Pass
827.99	V	-72.91	-36.00	
3504.19	V	-63.80	-30.00	
5255.97	V	-54.21	-30.00	

LTE Band 3(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.78	Horizontal	-74.46	-36.00	Pass
771.21	H	-74.60	-36.00	
3502.90	H	-68.04	-30.00	
5252.07	H	-58.39	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.49	Vertical	-74.38	-36.00	Pass
858.69	V	-71.50	-36.00	
3503.59	V	-68.50	-30.00	
5251.06	V	-58.87	-30.00	





LTE Band 3(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.35	Horizontal	-77.67	-36.00	Pass
882.41	H	-71.11	-36.00	
3500.61	H	-60.27	-30.00	
5255.33	H	-51.01	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.45	Vertical	-80.91	-36.00	Pass
806.21	V	-75.55	-36.00	
3501.90	V	-62.11	-30.00	
5253.77	V	-53.70	-30.00	

LTE Band 3(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.47	Horizontal	-70.70	-36.00	Pass
960.57	H	-73.62	-36.00	
3502.90	H	-62.68	-30.00	
5254.58	H	-51.85	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.65	Vertical	-71.57	-36.00	Pass
728.17	V	-79.35	-36.00	
3504.41	V	-63.17	-30.00	
5253.15	V	-59.37	-30.00	





LTE Band 7(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.52	Horizontal	-71.38	-36.00	Pass
896.02	H	-79.53	-36.00	
5072.47	H	-65.27	-30.00	
7689.62	H	-54.03	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.35	Vertical	-71.18	-36.00	Pass
850.11	V	-80.32	-36.00	
5072.35	V	-67.57	-30.00	
7686.03	V	-55.13	-30.00	

LTE Band 7(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.05	Horizontal	-78.63	-36.00	Pass
932.77	H	-74.28	-36.00	
5074.87	H	-64.67	-30.00	
7685.54	H	-57.62	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.46	Vertical	-80.17	-36.00	Pass
716.55	V	-75.46	-36.00	
5074.66	V	-68.93	-30.00	
7686.78	V	-58.35	-30.00	





LTE Band 7(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.75	Horizontal	-76.41	-36.00	Pass
968.60	H	-74.07	-36.00	
5071.71	H	-63.55	-30.00	
7686.33	H	-51.65	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.47	Vertical	-72.27	-36.00	Pass
885.80	V	-71.99	-36.00	
5075.80	V	-66.92	-30.00	
7685.12	V	-55.19	-30.00	

LTE Band 7(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.07	Horizontal	-78.03	-36.00	Pass
734.56	H	-79.10	-36.00	
5070.71	H	-62.50	-30.00	
7688.58	H	-56.93	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.00	Vertical	-70.54	-36.00	Pass
772.10	V	-74.95	-36.00	
5074.31	V	-64.29	-30.00	
7690.58	V	-51.44	-30.00	





LTE Band 8(1.4MHz, RB allocation=6): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.12	Horizontal	-77.15	-36.00	Pass
920.41	H	-70.57	-36.00	
1792.19	H	-65.38	-30.00	
2695.15	H	-53.92	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.48	Vertical	-76.24	-36.00	Pass
980.75	V	-77.90	-36.00	
1798.52	V	-62.18	-30.00	
2693.46	V	-50.41	-30.00	

LTE Band 8(1.4MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.39	Horizontal	-76.96	-36.00	Pass
928.66	H	-80.40	-36.00	
1800.27	H	-65.47	-30.00	
2695.00	H	-58.20	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.17	Vertical	-80.08	-36.00	Pass
971.54	V	-80.23	-36.00	
1796.07	V	-64.79	-30.00	
2691.21	V	-54.51	-30.00	





LTE Band 8(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.08	Horizontal	-79.05	-36.00	Pass
779.10	H	-80.39	-36.00	
1793.17	H	-66.40	-30.00	
2692.84	H	-56.16	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
52.81	Vertical	-78.90	-36.00	Pass
939.14	V	-72.05	-36.00	
1798.00	V	-62.89	-30.00	
2690.79	V	-50.61	-30.00	

LTE Band 8(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.83	Horizontal	-74.45	-36.00	Pass
983.70	H	-80.69	-36.00	
1797.67	H	-64.74	-30.00	
2694.96	H	-51.45	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.78	Vertical	-79.60	-36.00	Pass
869.84	V	-75.90	-36.00	
1790.36	V	-61.05	-30.00	
2690.36	V	-54.59	-30.00	





LTE Band 8(10MHz, RB allocation=50): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.13	Horizontal	-74.61	-36.00	Pass
984.46	H	-80.25	-36.00	
1796.95	H	-66.36	-30.00	
2693.38	H	-55.78	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.26	Vertical	-74.21	-36.00	Pass
858.61	V	-78.61	-36.00	
1795.75	V	-70.11	-30.00	
2692.63	V	-59.82	-30.00	

LTE Band 8(10MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.50	Horizontal	-78.87	-36.00	Pass
781.49	H	-70.72	-36.00	
1797.50	H	-64.55	-30.00	
2695.83	H	-51.58	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.80	Vertical	-78.61	-36.00	Pass
712.70	V	-78.71	-36.00	
1796.84	V	-69.68	-30.00	
2695.18	V	-59.72	-30.00	





LTE Band 20(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.57	Horizontal	-73.37	-36.00	Pass
799.97	H	-78.40	-36.00	
1695.05	H	-63.44	-30.00	
2540.35	H	-51.52	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.76	Vertical	-80.22	-36.00	Pass
704.62	V	-78.39	-36.00	
1691.10	V	-66.60	-30.00	
2542.40	V	-57.93	-30.00	

LTE Band 20(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.61	Horizontal	-73.21	-36.00	Pass
797.48	H	-79.18	-36.00	
1700.06	H	-63.57	-30.00	
2544.69	H	-54.80	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.74	Vertical	-73.72	-36.00	Pass
822.08	V	-78.72	-36.00	
1698.73	V	-67.79	-30.00	
2545.51	V	-53.09	-30.00	





LTE Band 20(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.42	Horizontal	-72.17	-36.00	Pass
911.49	H	-72.80	-36.00	
1693.35	H	-64.87	-30.00	
2542.84	H	-56.04	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.71	Vertical	-76.32	-36.00	Pass
754.64	V	-79.48	-36.00	
1694.45	V	-65.52	-30.00	
2545.83	V	-50.27	-30.00	

LTE Band 20(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.43	Horizontal	-77.51	-36.00	Pass
919.59	H	-73.51	-36.00	
1697.93	H	-60.47	-30.00	
2545.55	H	-56.10	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
52.96	Vertical	-76.32	-36.00	Pass
795.79	V	-70.05	-36.00	
1697.45	V	-70.41	-30.00	
2544.39	V	-50.29	-30.00	





LTE Band 28(3MHz, RB allocation=15): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.45	Horizontal	-74.45	-36.00	Pass
917.78	H	-75.98	-36.00	
1448.36	H	-66.42	-30.00	
2178.22	H	-55.37	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.69	Vertical	-70.75	-36.00	Pass
934.19	V	-71.31	-36.00	
1451.92	V	-61.32	-30.00	
2174.29	V	-56.16	-30.00	

LTE Band 28(3MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.25	Horizontal	-72.14	-36.00	Pass
732.38	H	-77.00	-36.00	
1447.58	H	-63.30	-30.00	
2175.71	H	-56.11	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.10	Vertical	-79.61	-36.00	Pass
801.71	V	-78.20	-36.00	
1446.65	V	-69.73	-30.00	
2180.71	V	-52.19	-30.00	





LTE Band 28(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
54.81	Horizontal	-76.08	-36.00	Pass
875.44	H	-79.35	-36.00	
1455.25	H	-63.88	-30.00	
2172.56	H	-55.77	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
54.90	Vertical	-72.85	-36.00	Pass
856.79	V	-70.20	-36.00	
1447.40	V	-63.72	-30.00	
2170.21	V	-60.02	-30.00	

LTE Band 28(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.95	Horizontal	-75.89	-36.00	Pass
773.53	H	-71.62	-36.00	
1455.37	H	-66.07	-30.00	
2173.66	H	-51.82	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.25	Vertical	-71.93	-36.00	Pass
936.64	V	-73.93	-36.00	
1455.39	V	-65.38	-30.00	
2171.33	V	-58.35	-30.00	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



LTE Band 28(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.65	Horizontal	-76.41	-36.00	Pass
935.68	H	-80.37	-36.00	
1450.53	H	-69.29	-30.00	
2171.51	H	-51.31	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
54.34	Vertical	-80.62	-36.00	Pass
938.75	V	-74.76	-36.00	
1452.92	V	-67.17	-30.00	
2179.35	V	-51.95	-30.00	

LTE Band 28(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.47	Horizontal	-78.68	-36.00	Pass
849.92	H	-78.15	-36.00	
1455.51	H	-67.01	-30.00	
2180.50	H	-60.34	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.34	Vertical	-79.36	-36.00	Pass
981.86	V	-76.25	-36.00	
1450.73	V	-63.15	-30.00	
2172.23	V	-56.07	-30.00	





LTE Band 38(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
52.63	Horizontal	-77.12	-36.00	Pass
941.34	H	-70.31	-36.00	
5195.29	H	-70.02	-30.00	
7791.98	H	-57.98	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.42	Vertical	-78.91	-36.00	Pass
801.38	V	-76.81	-36.00	
5190.40	V	-66.85	-30.00	
7794.93	V	-54.21	-30.00	

LTE Band 38(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
54.24	Horizontal	-79.25	-36.00	Pass
883.89	H	-77.81	-36.00	
5192.37	H	-61.01	-30.00	
7794.47	H	-53.08	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.03	Vertical	-77.55	-36.00	Pass
769.87	V	-75.94	-36.00	
5194.40	V	-61.44	-30.00	
7792.82	V	-54.92	-30.00	





LTE Band 38(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
54.17	Horizontal	-80.69	-36.00	Pass
747.16	H	-75.03	-36.00	
5192.80	H	-62.38	-30.00	
7790.00	H	-56.89	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.76	Vertical	-80.98	-36.00	Pass
973.08	V	-75.30	-36.00	
5190.66	V	-61.80	-30.00	
7794.09	V	-50.08	-30.00	

LTE Band 38(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
52.38	Horizontal	-72.23	-36.00	Pass
983.90	H	-75.81	-36.00	
5193.70	H	-61.48	-30.00	
7791.10	H	-55.66	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.81	Vertical	-74.97	-36.00	Pass
823.10	V	-79.76	-36.00	
5191.51	V	-62.96	-30.00	
7795.85	V	-59.41	-30.00	

-----THE END OF REPORT-----

