




Our Ref: Registration/CRS 2023-6528/R-41279722

Date:13-Feb-2024

Subject : Licence Document

MANUFACTURING UNIT :	UMEOX INNOVATIONS CO., LTD REGISTERED ADDRESS: 1901, BLOCK A, BUILDING 8, SHENZHEN INTERNATIONAL INNOVATION VALLEY, DASHI 1ST ROAD, XIII STREET, NANSHAN DISTRICT, SHENZHEN SHENZHEN, China-518000 chris.shao@umeox.com 8675526569880	
-------------------------	---	---

Dear Sir,

1. With reference to your Application, we are pleased to inform you that it has been decided to grant you licence as per details given below :

Product Category :	SEALED SECONDARY CELLS/BATTERIES CONTAINING ALKALINE OR OTHER NON-ACID ELECTROLYTES FOR USE IN PORTABLE APPLICATIONS PART 2 LITHIUM SYSTEMS
Product Name :	SEALED SECONDARY PORTABLE LITHIUM SYSTEM BATTERIES
IS NO :	IS 16046 (PART 2) : 2018 / IEC 62133-2 : 2017
Brand (As Declared by Manufacturer) :	UMEOX
Model :	[Brand -> UMEOX, Models -> 612726]
Factory Address :	REGISTERED ADDRESS: 1901, BLOCK A, BUILDING 8, SHENZHEN INTERNATIONAL INNOVATION VALLEY, DASHI 1ST ROAD, XIII STREET, NANSHAN DISTRICT, SHENZHEN SHENZHEN, China-518000

2. The Licence is being granted for your unit located at the address and for the brand and models mentioned at serial no 1 above.

3. The number assigned to this Licence is **R-41279722** which has been made operative from **13-Feb-2024** and is valid upto **12-Feb-2026** . The Licence Number should invariably be referred to in your future correspondence.

4. The rights and privileges under the licence shall not be exercised by any other factory / organization at any other location. This licence is not transferable. In the event of shifting of the manufacturing machinery from the registered premises to some other place use of the Licence Number shall be stopped and BIS shall be informed.

5. The licensee shall comply with the provisions of the Act, rules and regulations framed thereunder and as amended from time to time.

6. The licensee shall follow the guidelines for the use of Standard Mark and labeling requirements as per Annex-I.

7. The licensee shall not use the licence in any manner which contravenes the provisions of Act, rules and regulations framed thereunder and as amended from time to time.

8. Upon expiry of validity, stoppage or suspension or cancellation of licence, you shall discontinue forthwith the self declaration of conformity to the relevant Indian Standard(s) and withdraw all promotional and advertising matter which contains any reference thereto.

9. As per your declaration, **CHETAN SHARMA, Director, ORNATE QUALITY SERVICES PRIVATE LIMITED(Address- HOUSE NO. 8, GALI NO. 3, MOLARBAND EXTN.,, BADARPUR, South Delhi, Delhi, 110044, Delhi)** is your authorized Indian representative. Any intended change in the name of the Indian representative ought to be brought to our notice immediately along with requisite fees and document.

10. For renewal of licence, the licensee shall have to apply to BIS three months in advance before expiration of the licence and application form for renewal is available on BIS website

11. The licence is not transferable. Kindly acknowledge receipt of this letter.

Thanking you,

Yours faithfully,
(Jainendra Kumar)
Scientist-D
Telfax : +91-11-23230856
E-mail: registration@bis.gov.in

Note: This is a system generated letter. Hence signature is not required.
To verify authentication of letter, kindly scan the QR code on this letter.

Annex - 1

The guidelines for use of Standard Mark for Scheme-C are per 3(1) of BIS (Conformity Assessment) Regulations,2017 are given below:

- i) The monogram of the 'Standard Mark' consists of the pictorial representation, drawn in the exact style as indicated in the figure in the figure in Annexure I. Its photographic reductin and enlargement is permitted.
- ii)The 'Standard Mark' can be displayed in single colour or multi-colour as per the details given below. The colour scheme for the Standard Mark to be used in multi colour shall be use as indicated below.
- iii) The licensee shall diplay the 'Standard Mark' on the article and/or the packaging, as the case may be, in a manner so as to be easily visible. It shall be legible, indelible and non-remobable. Further, the durability of marking shall be as per the provisions of the relevant Indian Standard, wherever applicable. The diplay of IS number, Registration number and words shall not be less than Arial forn size 6.
- iv) Any device with a integrated display sceen may present the Standard Mark electronically (e-labelling) in lieu of a physical presentation on the product.

Technical drawing of a rectangular sign with rounded corners. The sign features a large stylized 'S' in the center and the text 'R-12345678' at the bottom. The drawing includes numerous dimensions and labels for various parts of the sign.

Dimensions:

- Overall width: 240.49 mm
- Overall height: 175.48 mm
- Top-left corner radius: 27.03 mm
- Top-right corner radius: 27.03 mm
- Bottom-left corner radius: 27.03 mm
- Bottom-right corner radius: 27.03 mm
- Top-left corner radius: 27.03 mm
- Top-right corner radius: 27.03 mm
- Bottom-left corner radius: 27.03 mm
- Bottom-right corner radius: 27.03 mm
- Top-left corner radius: 27.03 mm
- Top-right corner radius: 27.03 mm
- Bottom-left corner radius: 27.03 mm
- Bottom-right corner radius: 27.03 mm

Labels:

- B1:** 240.49 mm
- B2:** 175.48 mm
- B3:** 66.26 mm
- B4:** 12.00 mm
- B5:** 8.24 mm
- H1:** 200.00 millimeters
- H2:** 100.00 mm
- H3:** 39.37 mm
- H4:** 21.69 mm
- H5:** 29.12 mm
- L1:** 91.00 millimeters
- L2:** 84.31 mm
- L3:** 19.16 mm
- L4:** 40.47 mm
- L5:** 3.36 mm
- D1:** 23.51 millimeters
- D2:** 23.53 millimeters
- D3:** 7.52 mm
- D4:** 19.16 mm
- D5:** 42.49 mm
- D6:** 81.06 mm

Figures:

- fig A:** Top view of the sign.
- fig B:** Side view of the sign.

H1	200
H2	100
H3	39.3
H4	21.6
H5	17.7
L1	91.0
L2	84.3
L3	25.2
L4	40.4
L5	3.36
D1	23.5
D2	23.5
D3	7.52
D4	19.6
D5	42.4
D6	8.57
B1	240.49
B2	175.48
B3	66.26
B4	12.00
B5	8.24

a) For printing purposes, colours shall be “Oriental Blue” and “Monopol Red” as per IS 1222:1992. ‘Ink, duplicating for twin cylinder rotary machines (third revision)’

b) For sign board purposes, colours shall be “French Blue” (No.166) Red” (No.537) as per IS 5:1994 “Colours for ready mixed paints and enamels (fourth revision)”.

The font style and size used is Arial-85 pt.

IS -----



R - XXXXXXXXX

For details information on BIS, consult the e-BIS Portal (www.manakonline.in).
Please use BIS CARE APP for verification of ISI-marked goods and hallmarked gold jewellery.